

IN3140 Series

InFocus

Professional 3D Network Projectors

Part #s: IN3144, IN3146, IN3148HD

High-brightness, high-connectivity IN3140 Series projectors bring superior performance to your meeting room or classroom at a price that fits your budget. Get incredible image quality and smooth video playback through two HDMI ports. Easily manage the IN3140 Series over your network and easily install them with AMX and Crestron room control systems.



Why Buy the IN3140 Series?

- Up to 1080p (1920 x 1080) native resolution
- 5000 lumens
- 1.5x optical zoom
- 3D support for Blu-ray and more
- 10W speaker
- 2 1.4 HDMI, VGA and more
- Network Monitoring

IN3144	IN3146	IN3148HD
XGA (1024×768) 5000 lumens Throw: 1.83 - 2.75	WXGA (1280×800) 5000 lumens Throw: 1.46 - 2.20	1080p (1920×1080) 5000 lumens Throw: 1.46 - 2.20



Connectivity

HDMI v1.4a x 2	USB mini (for service)
VGA x 2	3.5mm Microphone
Composite	VGA Out
S Video	3.5mm 12V Screen trigger
3.5mm Input	USB-A 5V1.5A
RCA L/R audio	3.5mm Output

High Connectivity

IN3140 Series projectors are loaded with connectivity options, including two HDMI ports and multiple audio ports. Project from PCs, Macs, video sources, tablets and smartphones.

Immersive 3D

The IN3140 Series incorporates 3D Triple Flash technology and supports multiple forms of 3D, including HDMI, Blu-Ray, 3D broadcasting, video games and NVIDIA 3DTV PC connectivity. Display 3D in 1080p full HD over HDMI. Compatible with 144Hz DLP Link™ 3D glasses.

Impressive Image Quality

With 5000 lumens, high contrast, six-segment color wheel, and BrilliantColor™ DLP imaging, the IN3140 Series projects big, bright, colorful images with the lights on and the blinds open. The 1.5:1 zoom ratio and extensive throw ratio mean these projectors work in a wide variety of rooms.

Network Support and Digital Control

Remotely manage and support your projector from a single computer via your existing network with free ProjectorNet 4.0 software from InFocus. Crestron Roomview enables instant, intuitive operation without a control processor or custom programming. AMX Device Discovery lets an AMX controller detect the projector dynamically and configure it for the remote control.

Specifications*

	IN3144	IN3146	IN3148HD
Native Resolution	XGA (1024x768)	WXGA (1280x800)	1080p (1920x1080)
Display Technology	DLP 0.55 S450	DLP 0.65" S450	DLP 0.65" S600
Lamp Power	310W (Normal Mode), 245W (Low Power), 93W (Dynamic Mode)		
Lamp Life (Dyn/Low/Normal)	3,500 hours (Normal Mode), 4,500 hours (Low Power), 6,000 hours (Dynamic Mode)		
Brightness (Normal/Eco)	5000 lumens Normal Mode (4000 lumens Eco Mode)		
Contrast Ratio	16000:1		
Aspect Ratio	4:3 Native, Supports 16:10, 16:9, 2.35:1	16:10 Native, Supports 4:3, 16:9, 2.35:1	16:9 Native, Supports 4:3, 16:10, 2.35:1
Projection Lens (f-stop)	2.42 ~ 2.97		
Color Wheel	6 Segment		
Lens Type	Manual zoom and focus		
Projection Distance	1.2m - 10.0m		
Lens: Throw Ratio Zoom Ratio	1.83 - 2.75 1.5:1	1.46 - 2.20 1.5:1	
Image Width	21.5"~270"	25.3"~318"	
Projection Offset	14%	11%	15%
Keystone Vertical	+/-40°		
Input Sources	HDMI v1.4a x 2, VGA x 2, Composite, S Video, 3.5mm Input, RCA L/R audio, USB mini (for service), 3.5mm Microphone		
Output Sources	VGA Out, 3.5mm 12V Screen trigger, USB-A 5V1.5A, 3.5mm Output		
Control	RS232, RJ45		
Video Compatibility	Standard (NTSC, NTSC 4.43, PAL / M / N, SECAM), SD (480i, 480p, 576i, 576p), HD (720p, 1080i, 1080p)		
Synch Scan Frequency			
Horizontal:	15K~91.4K Hz		
Vertical:	24~30Hz, 47~120 Hz		
Power Consumption (Dynamic/Eco/Normal)	93w~410W / 320w / 410w		
Audible Noise	30 dB Eco Mode		
Operating Temperature	41 - 104° F / 5 - 40° C		
Operating Conditions	2500ft ~ 5,000ft - 35 Degrees Celsius 5,000ft ~ 10,000ft - 25 Degrees Celsius		
Menu Languages	English, French, German, Spanish, Italian, Norwegian, Dutch, S.Chinese, T. Chinese, Korean, Swedish, Russian, Finnish, Polish, Turkish, Danish, Arabic, Indonesian, Persian, Portuguese, Vietnamese, Czech, Hungarian		
Speakers	10W Mono		
Dimensions - WxDxH	314 mm x 216 mm x 126 mm		
Product Weight	6.9 lbs / 3.1 kg		
Shipping Dimensions (W x D x H)	15.4 x 14.5 x 8.2 in / 391.2 x 368.3 x 208.3 mm		
Shipping Weight	10.3 lbs / 4.7 kg		
Ships with - Accessories	User Manual (CD), Quick Start Guide, Safety/Reg Card, VGA Cable (1.8m), Regional Pwr Cord (1.8m), Remote Control (NO BATTERIES)		
Warranty	2 year (product), 6 months (lamp), 90 days (accessories)		

Optional Accessories

Replacement Lamp (SP-LAMP-098)
 Universal Ceiling Mount (PRJ-MNT-UNIV)
 LiteShow Wireless Adapter (INLITESHOW4)
 Carrying Case (CA-SOFTCASE-MTG)
 ATA Travel Case (CA-ATA-MTG2)
 Extended warranties (EPW-PJM1, EPW-PJM2)
 XPAND DLP Link 3D Glasses (X103-EDUX3-R1)
 Cables and adapters