Xerox[®] AltaLink[®] Multifunction Printers



B8145/B8155/B8170



AltaLink[®] B8100 Series Multifunction Printers are built on Xerox[®] ConnectKey[®] Technology. For more information, go to **www.connectkey.co.uk**.

System Specification	AltaLink® B8145	AltaLink® B8155	AltaLink® B8170	
Speed ¹	Up to 45 ppm	Up to 55 ppm	Up to 72 ppm	
Monthly Duty Cycle ²	Up to 200,000 pages	Up to 250,000 pages	Up to 300,000 pages	
Hard Drive/Processor/ Memory	Minimum 128 GB SSD/ Optional: 500 GB HDD/Intel Atom [®] Quad Core 1.91 GHz/4 GB system memory			
Connectivity	Ethernet 10/100/1000 Base-T, High-speed USB 2.	0 direct print, Wi-Fi/Wi-Fi Direct with optional Xerox	[®] Dual Band Wireless Kit, NFC, Bluetooth (iBeacon)	
Controller Features	Unified Address Book, Remote Control Panel, Confi	guration Cloning, Fleet Orchestrator, Configuration \	Watchdog	
Copy and Print				
Copy and Print Resolution	Copy: Up to 600 x 600 dpi; Print: Up to 1200 x 24	400 dpi		
First-Print-Out Time (as fast as)	3.8 seconds	3.2 seconds	3.0 seconds	
First-Copy-Out Time (as fast as) (from platen/ warmed-up state)	4.4 seconds	3.7 seconds	3.2 seconds	
Page Description Language	Adobe® PostScript® 3 [™] , Adobe® PDF, PCL® 5c/PCL® 6			
Print Features	Print from USB, Print from cloud repositories (Dropbox, One Drive and Google Drive), Encrypted Secure Print, Xerox® Earth Smart Driver Settings, Job Identification, Booklet Layout, Store and Recall Driver Settings, Bi-directional Real-time Status, Scaling, Job Monitoring, Application Defaults, Two- sided Printing (as default), Hold All Jobs, Long Sheet (Banner) Printing, Print Around, Print on Alternate Paper; Optional: Print from and Scan to Xerox® DocuShare® Go content management.			
Mobile and Cloud Ready				
Mobile Connectivity	Near-Field Communication (NFC); Optional: Wi-Fi	Direct, Wi-Fi (802.11 b/g/n/ac), AirPrint (iOS) includ	ling iBeacon (Bluetooth)	
Mobile Printing	AirPrint®, Mopria®, Xerox® Print Service (Android), Xerox® @PrintByXerox App; Optional: Xerox® Workplace Mobile App (iOS/Android)			
Mobile Scanning	AirPrint®, Mopria®; Optional: Xerox® Workplace Mobile App (iOS/Android)			
Mobile Apps and Xerox® App Gallery	Automate everyday processes with apps that translate, redact, eSign, personalise print, convert, route, collaborate and communicate. Visit www.xerox.co.uk/en-gb/connectkey/workplace-apps to find apps by industry or workflow. Software and services: Xerox® DocuShare® (xerox.co.uk/ecm), XMPie [®] (www.xerox.co.uk/en-gb/digital-printing/workflow-software/printing-software/xmpie-personalised- communication-software), Xerox [®] Workplace Solutions (www.xerox.co.uk/en-gb/office/print-management-solutions).			
Xerox® Workplace Suite and Xerox® Workplace Cloud	Optional: Xerox [®] Workplace Suite is a modular set of workflows designed to save customers time and money by providing effective control over their print fleet, while enabling worker productivity and mobility through a set of robust workflows. Xerox enables ultimate customer flexibility by offering these capabilities in both an on-premise server version (Workplace Suite) and with a cloud based-version (Workplace Cloud) of this solution.			

Scan	
Standard Features	Destinations: Scan to USB/Email/Network (FTP/SMB), HTTP, HTTPS, SFTP destinations; File Formats: PDF, PDF/A, JPEG, TIFF; Convenience Features: Scan Preview, Scan to Home, Searchable PDF, Single/Multi-Page PDF/TIFF, Password Protected PDF, Unified Address Book, Optical Character Recognition (OCR), Scan to Folder, 1-Touch Apps, TWAIN Support
Optional Features	Scan To cloud repositories (Dropbox, One Drive and Google Drive) ³ , Xerox [®] Scanning App for DocuShare [®] , other solutions available through various Xerox Business Innovation Partners at www.xerox.co.uk/en-gb/office/printer-software , Print from and Scan to Xerox [®] DocuShare [®] Go content management.
Fax	
Standard Features	Internet Fax, Network Server Fax Enablement, Fax Build Job
Optional Features	Walk-up Fax (one-line and two-line options available, includes LAN Fax, Direct Fax, Fax Forward to Email or SMB Share)
Security	
Standard Features	802.1 x, IPsec, HTTPS, SFTP and Encrypted Email, McAfee® Embedded Control Whitelisting, McAfee® ePolicy Orchestrator®, McAfee Enterprise Security Manager ³ , LogRhythm SIEM ³ , Network Authentication, SNMPv3, SHA-256 Hash Message Authentication, TLS1.1/1.2/1.3 Security Certificates utilising ECDSA, Automatic Self-signed Certificate, Cisco® Identity Services Engine (ISE) integration, automated threat response through McAfee® DXL/Cisco® pxGrid integration, Local Authentication (Internal Database), FIPS 140-2. User Access and Internal Firewall, Port/IP/Domain Filtering, Audit Log, Access Control, User Permissions, Configuration Watchdog, TPM, Trusted Boot, Encrypted Storage Drive (AES 256-bit, FIPS 140-2), Firmware Verification, Job Level Encryption via HTTPS and Drivers, Signed Email Under evaluation for Common Criteria Certification (ISO 15408), Encrypted Secure Print
Optional Features	McAfee® Integrity Control, Smart Card Enablement Kit (CAC/PIV/.NET) ⁴ , Xerox [®] Integrated RFID Card Reader, Encrypted Hard Disk (AES 256-bit, FIPS 140-2) with Image Overwrite, Xerox [®] Workplace Cloud/Suite Print Management and Content Security; learn more at www.xerox.co.uk/en-gb/office/print-management-solutions
Print Management	
Standard Features	Xerox® Standard Accounting (Copy, Print, Scan, Fax, Email), Network Accounting Enablement
Optional Features	Xerox® Workplace Cloud/Suite, other network accounting solutions available through various Xerox Business Innovation Partners. Xerox® Virtual Print Management Service; learn more at www.xerox.co.uk/en-gb/office/printer-software#printmanagement

Features and Accessories

Single-Pass Duplex Automatic Document Feeder (DADF) saves time by simultaneously scanning both sides of twosided documents with up to 270 impressions per minute (ipm).



USER INTERFACE



Intuitive Tablet-like 10.1-inch Colour Touchscreen is customisable and lets you perform tasks in just a few taps. Try it out at xerox.com/AltaLink8100UI.

INNOVATIVE TECHNOLOGIES





Xerox[®] Integrated RFID Card Reader (optional) adds card-based authentication with support for over 90 access cards.

Near Field Communication (NFC) Tap-to-Pair allows users to tap their mobile devices to the AltaLink® B8100 Series user panel and quickly connect with the MFP.

Smart Proximity Sensor detects when users are nearby. It conserves energy during inactive periods and automatically activates the device when a user approaches.



Office Finisher (optional) provides advanced finishing functions, optional crease/score and saddle-stitch booklet, making it capable of 60-page booklets (2 to 15 sheets). Business Ready

Business Ready (BR) Finisher (optional) gives you advanced finishing functions at a great value.



C-Fold/Z-Fold Unit (optional) adds C-fold, Z-fold and Z-half-fold to the BR Finisher or BR Booklet Maker Finisher.



BR Booklet Maker Finisher (optional) creates 64-page saddle-stitched booklets (2 to 16 sheets).



Convenience Stapler (optional) staples up to 50 sheets of 20 lb./75 gsm media.

PAPER INPUT⁵

Two 520-sheet Adjustable Trays (common with all configurations). Tray 1 handles media sizes up to A3 and Tray 2 handles media sizes up to SRA3.



Envelope Kit (optional – replaces Tray 1) provides feeding of up to 60 envelopes.



High Capacity Tandem Tray Configuration holds a total paper capacity of up to 3,140 sheets.



Im A TEL

High Capacity Feeder (optional) holds 3,000 sheets of A4 paper, increasing the maximum paper capacity to 6,140 sheets.



LONG SHEET PRINTING

Long Sheet Feed Kit (optional) provides the ability to print up to 320 x 1,320 mm media.





Dual Offset Catch Tray (available when no finishers are installed; Single Offset Catch Tray with finishers).



Integrated Office Finisher (optional with B8145/B8155) provides 500-sheet stacking and 50-sheet, 2-position stapling.

Device Specification			
Control Panel Languages	US English, International English, International Fre Finnish, Turkish, Greek, Russian, Czech, Polish, Hung	ench, Italian, German, International Spanish, Dutch, I garian, Romanian, Catalan, Arabic	Brazilian Portuguese, Swedish, Norwegian, Danish,
Accessories			
Optional	Finisher Convenience Stapler (includes Work Surface ⁶) Integrated Office Finisher (Available with AltaLink' Office Finisher Booklet Maker for Office Finisher Hole Punch (2/3, 2/4, Swedish) Office Finisher Smart Card Enablement Kit ⁴ Walk-up Fax (One- or Two-line options, includes LA Wi-Fi/Wi-Fi Direct with Dual Band Wireless Kit Bluetooth Kit McAfee [®] Integrity Control Enablement Kit USB Keyboard/Shelf Kit Verox [®] Integrated RFID Card Reader Kit Unicode Font Kit Foreign Device Interface (Also known as Auxiliary, Long Sheet Feed Kit (banner printing) 500GB HDD Scan To Cloud Enablement Kit	nsport Kit) C-fold/Z-fold Unit for BR Finisher or BR Bo ® B8145, B8155) N Fax) Access Device) Interface for third-party access contro	ol devices, such as coin machines and card readers
Electrical Requirements	AltaLink® B8145	AltaLink® B8155	AltaLink® B8170
North America	Voltage: 110-127 VAC +/- 10% Frequency: 50/60 Hz +/- 3%, 15 A		Voltage: 110-127 VAC +/- 10% Frequency: 50/60 Hz +/- 3%, 20 A
Europe	Voltage: 220-240 VAC +/- 10% Frequency: 50/60 Hz +/- 3%, 10 A		Voltage: 220-240 VAC +/- 10% Frequency: 50/60 Hz +/- 3%, 10 A

Device Specification (contin	ued)		
Power Consumption	AltaLink® B8145	AltaLink® B8155	AltaLink® B8170
Running (Average)	115V: 717 watts 230V: 674 watts	115V: 806 watts 230V: 760 watts	115V: 929 watts 230V: 908 watts
Standby Mode	115V: 71 watts 230V: 71 watts	115V: 72 watts 230V: 70.3 watts	115V: 91.1 watts 230V: 79 watts
Auto Off/Sleep Mode	115V: 0.67 watts 230V: 0.71 watts (Default time to sleep mode = 0 minutes)	115V: 0.67 watts 230V: 0.71 watts (Default time to sleep mode = 0 minutes)	115V: 0.68 watts 230V: 0.75 watts (Default time to sleep mode = 0 minutes)
Warm-up (from Off)	As fast as 85 seconds		
Recovery from Sleep	As fast as 4.5 seconds		
Operating Environment			
Required Temperature Range	50 to 82° F/10 to 28° C		
Required Relative Humidity	15% to 85%		
Sound Power Levels	Operating: 63.7/64.2 dB(A) Standby: 4.0/4.0 dB(A)	Operating: 65.2/67.3 dB(A) Standby: 4.3/4.3 dB(A)	Operating: 70.4 dB(A) Standby: 4.3 dB(A)
Dimensions and Weight			
Base Configuration	Width: 620 mm Depth: 723 mm Height: 1,130 mm Weight: 129.5 kg		Width: 620mm Depth: 793mm Height: 1,169mm Weight: 144.8kg
With Office Finisher (with Booklet Maker)	Width: 1,207 mm Depth: 723 mm Height: 1,130 mm Weight: 168 kg		Width: 1,207mm Depth: 793mm Height: 1,169mm Weight: 184.2kg
Base Configuration with Business Ready (BR) Finisher	Widh: 1,395 mm Depth: 723 mm Height: 1,130 mm Weight: 173.4 kg		Width: 1,395mm Depth: 723mm Height: 1,169mm Weight: 188.4kg
Base Configuration with BR Booklet Maker Finisher	Width: 1,496.3 mm Depth: 723 mm Height: 1,130 mm Weight: 190.4 kg		Width: 1,496.3 mm Depth: 723 mm Height: 1,169 mm Weight: 205.6 kg
Base Configuration with BR Booklet Maker Finisher and C-fold/Z-fold Unit	Depth: 723 mm Height: 1,130 mm		Width: 1,632mm Depth: 723mm Height: 1,169mm Weight: 255.9kg
Base Configuration with BR Booklet Maker Finisher, C-fold/Z-fold Unit and High Capacity Feeder	Width: 2,361 mm Depth: 723 mm Height: 1,130 mm Weight: 271.6 kg		Width: 2,361mm Depth: 723mm Height: 1,169mm Weight: 287kg
System Certifications/Regul	atory Compliance		
Certifications	To view the latest list of certifications, go to xerox .	com/OfficeCertifications	

Paper Handling	AltaLink® B8145	AltaLink [®] B8155	AltaLink® B8170
Single-Pass Duplex Automa	tic Document Feeder (DADF)		
Capacity ⁵	130 sheets		250 sheets
Speed (Up to)	82 ppm black-and-white (simplex) 141 ipm black-and-white (duplex)		135 ppm black-and-white (simplex) 270 ipm black-and-white (duplex)
Paper Sizes Sensed	85 x 125 mm to 297 x 432 mm		
Weights	60 to 128 gsm		
Bypass Tray (Standard)			
Capacity ⁵	100 sheets		
Sizes	Custom Sizes: 89 x 98 mm to 320 x 1320 mm (SEF); Optional: Long Sheet Feed Kit (Banner Printing)		
Weights	52 to 300 gsm, Long sheets/banners (>19 in./48	3 mm) 28lb Bond - 120lb Index/106 - 220 gsm	
Media Types	Bond Card Stock Card Stock Reloaded Custom Envelopes Glossy Card Stock Reloaded Heavyweight Card Stock Reloaded Heavyweight Glossy Card Stock Reloaded Hole Punched Labels Letterhead Lightweight Card Stock Reloaded Lightweight Card Stock Reloaded Lightweight Glossy Card Stock Lightweight Glossy Card Stock Reprinted Reprinted Recycled Transparencies Long Sheets/Banners: Card Stock Reloaded		
Trays 1 and 2 (Standard)	Lightweight Card Stock Reloaded		
Capacity ⁵	520 sheets each		
Sizes	Tray 1: Custom Sizes: 140 x 182 mm to 297 x 432 Tray 2: Custom Sizes: 140 x 182 mm to SRA3 (SEI		
Weights	52 to 300 gsm		
Media Types	Bond Card Stock Card Stock Reloaded Custom Envelopes Glossy Card Stock Glossy Card Stock Reloaded Heavyweight Card Stock Reloaded Heavyweight Glossy Card Stock Heavyweight Glossy Card Stock Reloaded Hole Punched Labels Letterhead Lightweight Card Stock Lightweight Card Stock Reloaded Lightweight Glossy Card Stock Lightweight Glossy Card Stock Reloaded Plain Plain-Reloaded Preprinted Recycled Transparencies		

Paper Handling (continued)	AltaLink® B8145	AltaLink® B8155	AltaLink® B8170
High Capacity Tandem Tray	, (Available with all models)		
Capacity ⁵	Tray 3: 867 sheets Tray 4: 1,133 sheets		
Sizes	A4, JIS B5, LEF		
Weights	52 to 300 gsm		
Media Types	Bond Card Stock Custom Glossy Card Stock Hole Punched Labels Letterhead Lightweight Card Stock Lightweight Glossy Card Stock Plain Preprinted		
Envelope Tray (Optional - R	eplaces Tray 1)		
Capacity ⁵	Up to 60 envelopes		
Sizes	#10 Commercial (241.3 x 104.78),)/Monarch, DL, C5 Custom Sizes: 98 x 148 mm to 162 x 241 mm		
Weights	75 to 90 gsm		
High Capacity Feeder (HCF)	(Optional with all models)		
Capacity ⁵	3,000 sheets		
Sizes	Standard Sizes: A4 or B5 LEF		
Weights	52 to 300 gsm		
Total Capacity			
Device Total Capacity ⁵	High Capacity Tandem Tray Module: 3,140 sheets High Capacity Tandem Tray Module with High Cap	acity Feeder: 6,140 sheets	

Finishing	AltaLink® B8145	AltaLink® B8155	AltaLink® B8170
Output Trays (Standard) (I	oual Offset Catch Trays not availe	able with Integrated Office Finisher and limite	ed to one with Office Finisher and BR Finishers)
Stacking Tray Capacity ⁵	Dual Offset Catch Tray: Up to 250 Left Side Face up Tray: Up to100		
Integrated Office Finisher	(Optional with AltaLink® B8145/I	(88155)	
Stacking Tray Capacity ⁵	500 sheets of 80 gsm – A4 or 250	0 sheets of 80 gsm – A3	
Sizes	89 x 98 mm to 297 x 432 mm		
Weights	52 to 300 gsm		
Stapling		sheets (less than 90 gsm or (2) 220 gsm covers) 4 size sheets (less than 90 gsm or (2) 220 gsm cov	/ers)
Office Finisher (Optional)			
Stacking Tray Capacity ⁵	2,000 sheets unstapled or 1,000 s	sheets single stapled or 750 sheets dual stapled (A	44)
Stacking Tray Sizes	210 x 182 mm to 297 x 432 mm	1	
Weights	52 to 300 gsm		
Multiposition Stapling		sheets (less than 90 gsm or (2) 220 gsm covers) 4 size sheets (less than 90 gsm or (2) 220 gsm cov	vers)
Hole Punch (Optional)	North America: 2/3-hole punch Europe: 2/4-hole punch Optional: 4-hole "Swedish" punch		
Booklet Maker for Office F	nisher (Score/Crease, Saddle-stite	tch Staple) (Optional)	
Top Tray Capacity ⁵	40 booklets (2-15 sheets per book	oklet – 20 lb./80 gsm or less)	
Sizes	A4 SEF B4 SEF A3 SEF		
Saddle-Stitch Stapling	2-15 sheets/8-60 page booklet 60 to 256 gsm		
Score/Crease	1-15 sheets/unstapled 60 to 105 gsm		
Business Ready (BR) Finish	er (Optional) (Requires Horizonta	al Transport Kit)	
Capacity ⁵	Offsetting Top Tray: 500 sheets Stacking Stapling Tray: 3,000 shee 100 sets (dual or 4-position stapli	eets unstapled or ling) 216 x 356 mm, A3 or 200 sets (single-positior	n staple) A4
Sizes	100 x 148 mm x 320 x 488 mm f 182 x 203 mm to 320 x 488 mm B5 to A3 for stapling		
Weights	52 to 300 gsm		
Stapling	Single and multiposition stapling Auto stapling (50 sheets maximu Legal, A3, A4, B4 and B5 sizes sup	um) – 90 gsm	
Hole Punch	North America: 2/3-hole punch Europe: 2/4-hole punch Optional: 4-hole "Swedish" punch		
BR Booklet Maker Finisher	(Optional) (Requires Horizontal 1	Transport Kit)	
Cαpacity ^s	Offsetting Top Tray: 500 sheets o Stacking Stapling Tray: 1,500 sheets of A4/A3 unstapled 200 stapled sets of A4 (single-pos dual or 4-position stapling) or 100	l or sition stapling or	
Sizes	100 x 148 mm x 320 x 488 mm for top tray 182 x 203 mm to 320 x 488 mm for stacking B5 to A3 for stapling		
Weights	52 to 300 gsm		
Stapling	Single and multiposition stapling Auto stapling (50 sheets maximum) – 90 gsm Legal, A3, A4, B4 and B5 sizes supported		
Hole Punch	North America: 2/3-hole punch Europe: 2/4-hole punch Optional: 4-hole "Swedish" punch		
Booklet maker	Saddle-stitch 2 to 16 sheets (7 sh Bi-fold up to 5 sheets Legal, A3, A4 supported	neets at 106 to 176 gsm coated or 5 sheets at 177	' to 220 gsm coated)

Finishing (continued)	AltaLink® B8145	AltaLink [®] B8155	AltaLink® B8170	
C-fold/Z-fold Unit (Optiona	' I with BR Finisher and BR Booklet Maker Finishe	r)		
Турез	C-fold, Z-fold and Z-half-fold			
Capacity ⁵	40 sheets			
Sizes	C-fold and Z-fold: A4 SEF only Z-half-fold: A3 only	,		
Weights	64 to 90 gsm			
Output Trays	Envelope Tray: C-fold, Z-fold and Tri-fold Stacker Tray or Top Tray: Z-half-fold			
Convenience Stapler (Optic	onal - Includes Work Surface ⁶)			
Capacity ⁵	50-sheet stapling 5,000 staples Requires separate power outlet			
Сору	AltaLink [®] B8145	AltaLink® B8155	AltaLink [®] B8170	
First-Copy-Out Time (from platen/warmed up)	As fast as 4.4 seconds	As fast as 3.7 seconds	As fast as 3.2 seconds	
Sides (input:output)	1-1, 1-2, 2-2, 2-1			
Quantity	1 to 9,999			
Resolution (max)	Up to 600 x 600 dpi			
Reduction/Enlargement	Variable zoom from 25% to 400% in 1% increme	ents		
Concurrency	Program-ahead to allow job to be queued while in	itial job is processed (Copy, Print, Fax and Scan)		
Copy Features	Annotation and Bates [™] stamping Authentication for Services Auto Paper Select Auto Reduction & Enlargement (To fit selected pap Auto Tray Switching Automatic 2-sided/Duplex Booklet Creation Build Job (Enables page-level programming and al Collation Covers (Front only, front and back, back only, print Dividers (blank) Edge Erase Features Help (Intuitive text and graphic description ID Card Copy Image Quality Adjustments Image Shift (with Auto Centre option) Invert Image (negative or mirror image) Large Job Interrupt Multi-up (up to 15 columns by 15 rows) Sample Set Save Job Settings Single Colour Stapling Transparencies	so lets you proof each section or delete last section ed inside and out: Blank or Printed)	as the job is built)	

Print	AltaLink [®] B8145	AltaLink® B8155	AltaLink [®] B8170	
Resolution (up to)	1200 x 2400 dpi			
Print Features	LAN Fax (requires optional Fax Kit) Layout/Watermark N-up (up to 16 pages per sheet) Booklet Layout Long Sheet/Banner Finishing Fit to New Paper Size Hold All Jobs Paper Selection by Attribute Samp Saved Job Secure Print with Timed Deletion Special Pages (exception page pro Store and Recall Driver Settings	ution (Standard, Enhanced, High) her, Print ID in margins on first page only or all pa le Set gramming: covers, inserts, exception pages) th Smart Settings, Duplex, N-up, Turn-off Banner		
Print from USB	Allows walk-up printing from Type. Supports direct printing from comp Supported file formats: PDF, JPEG, Colour jobs can be printed as black	outer via Type B USB port TIFF, PS, PCL		
Operating Systems	Windows Server 2008 SP2 (32- and Windows Server 2008 R2 (64-bit) Windows Server 2012 and R2 (64- Windows Server 2019 (64-bit) Windows Server 2019 (64-bit) Windows 7 (32- and 64-bit) Windows 8 (32- and 64-bit) Windows 8.1 (32- and 64-bit) Windows 10 (32- and 64-bit) Windows 10 (32- and 64-bit) Mac OS 10.13, 10.14, 10.15 Fedora® Core Ubuntu®			
Network Protocols	TCP/IP: HTTP/HTTPS, Internet Prin Microsoft Windows Networking ov Bonjour®/AirPrint® IPv6 Most protocols not in use can be d		9100, IPv4/IPv6, WSD	
Font Capability	PCL: 93 scalable fonts, line printer of	and bitmap font (including Cyrillic font support) P	PostScript 3: 173 Type 1 fonts, 2 Multiple Master fonts	
Xerox® Global Print Driver®		A truly universal print driver that lets IT administrators install, upgrade and manage Xerox [®] and non-Xerox devices from a single driver. It provides a consistent, easy-to-use interface for end-users, reducing the number of support calls and simplifying print services management.		
Xerox [®] Pull Print Driver	single driver. The Xerox® Pull Print I		a single driver in a Pull Print environment. Uses a single queue and of printing assets. IT administrators no longer need to manage and Pharos® and others.	
Unified Address Book for	Fax, Internet Fax, Email and Scan t	0		
Features	Services supported: Fax, Internet For Maximum contacts: 5,000 Contacts: Supports 1 or more desti Favourites for quick access of all se	nations		

Scan	AltaLink® B8145	AltaLink® B8155	AltaLink® B8170	
Concurrency	Scan while the system is printing, concurrent jobs)	, copying, or while it is transferring scan to networl	k or fax jobs (priority is for return of scanned originals and printing	
Input Speed (up to)		82 ppm black-and-white and colour (simplex)135 ppm black-and-white and colour (simplex)141 ipm black-and-white and colour (duplex)270 ipm black-and-white and colour (duplex)		
Resolution	72 x 72 dpi to 600 x 600 dpi			
Bit Depth	1-bit (black-and-white), 8-bit (gre	eyscale), 24-bit (colour)		
Maximum Scan Area	A3	A3		
Scan Template Management	Support 250 scan templates Create Xerox® CentreWare® IS sc	Support 250 scan templates Create Xerox® CentreWare® IS scan templates and share via device cloning to other multifunction printers' confirmation sheet options		
Network Protocols	SFTP, FTP, SMB, HTTP, HTTPS			
File Compression		MMR compression – single or multiple pages) 1b (MRC, JPEG, G3 MH, G4 MMR, JBIG 2 Huffman	n, JBIG Arithmetic Compression, Deflate (for black-and-white and	
Document Management Fields (Metadata)	Metadata field consists of field	rk Scan to File Templates: adata fields per network scan to file templates and name, default value and other configurations er interface for variable data input	d unlimited fields within the template –	
Scan Features	Mixed Size Originals Scan Build Job Scan Preview Compression Quality/File Size Co Original Type (Photo and Text, Ph Auto Background and Shadow Su Size for Size (for mixed size origin TWAIN Support/WIA 2.0 Suppor Bound Originals Edge Erase Reduction/Enlargement Single Touch Scan buttons (up to	noto, Text, Map, Newspaper/Magazine) uppression ials) t		
Scan to Email (Standard)				
Scan Features	Email signatures (6 lines each a options Scan to Email S/MIME Encrypti Email signing (requires Smart C Auto send to self	ion	configurable), email Embedded Web Server confirmation sheet	
Directory Access	Address list via LDAP (Windows A	Active Directory, Exchange, Notes, Domino), Device	e Address Book	
Scan To				
Standard Features	Scan to USB Scan to Network Folder (using Secure FTP/HTTP/HTTPS) Scan to Home Scan to Network (using Secure FTP/HTTP/HTTPS) Scan to Email Scan to PC/Server Client (SMB or FTP) Scan to Mailbox			
Optional Features	Scan to Cloud Repositories (Dropbox, One Drive and Google Drive) ³			
Workflow Scanning (Optio	nal)			
Scanning Software	Autostore v7 eCopy ShareScan v5.2 eCopy ScanStation v5.2			
Scanning Apps and Xerox App Gallery		Drive, Microsoft OneDrive®, Microsoft Office 365™, in the Xerox App Gallery: xerox.com/AppGallery	Box®, Xerox® Workplace Mobile App (iOS/Android)	

Security	AltaLink® B8145	AltaLink® B8155	AltaLink [®] B8170
Features	 Expanded Authentication Network authentication to access Windows server 2012), NDS, LD/ Local Authentication (internal da Smart Card authentication – 144/ Secure Data Digitally signed PDF (when using Encrypted and authentication to Encrypted/Password Protected PE Secure Print (up to 10 digit PIN o Immediate Image Overwrite/Sec On Demand Image Overwrite/Sec On Demand Image Overwrite/Sec Expanded Authorisation SA access based on network cred Authorisation per user per service User Permissions required to access Configuration Watchdog (Monitor of Front USB Port 2 Rear USB Port 3 Scan to Mailbox enablement Fax Passcode length System timeout Show/Hide Login Name PostScript® Passwords Remote Services Setup Supplies/(Remote Services Setup Su	s device and/or device services via Kerberos (UN AP authentication tabase) k CAC/PIV Card Support (2048 bit certificate ke Smart Card authentication) SMTP server for Scan to Email DF (when using Email and Network Scan Temple r Network Authentication) urely delete jobs using approved algorithms ¹¹ theduled, Manual), includes sanitation of unuse ryption, TLS 1.1/1.2/1.3, IPPS, HTTPS, SFTP, SN entials esss Print and Print Features (e.g. time restriction: and remediate 29 security settings): ddresses, enablement, Recipient Group Preferen Consumables: Enablement Consumables: Software Download Consumables: Software Download Consumables: Daily Synchronisation Time Consumables: Daily Synchronisation Time Consumables: Automatically Send Diagnostic Ir grade) Enable/Disable // Disable Services inters ices on multifunction printers : in Network Accounting Reports : in Audit Logs v1.3, SNMP v1/v2/v3, HTTPs, 802.1X, SFTP elisting), McAfee [®] Integrity Control (optional) rts	IIX/Windows Server 2008), SMB (Windows Server 2008, sy)/.NET d area of disk ¹¹ MPv3 s) reflects in the print driver ces
Xerox® Integrated RFID Card Reader	Full System Common Criteria certifi	ied by NIAP under HD Protection Profile for Har	

Fax	AltaLink® B8145	AltaLink® B8155	AltaLink [®] B8170	
Network Server Fax Feature	25			
Compatibility	ITU (CCITT) group 3; Various Xerox Business Innovation Partner Solutions			
Maximum Scan Area	A3			
Fax Send Features	One- or Two-sided Scanning (up to A3) Add to Send List (200 numbers maximum) Build Job, Favourites, Delay Send (specific time) Original Type (photo, text or photo and text)			
Fax Print Features	One- or Two-sided Printing, Staple, Secure	Print		
Transmission Resolution	Superfine: 400 x 200 dpi (Scan at 600 x 600 dpi) Fine: 200 x 200 dpi Standard: 200 x 100 dpi			
Internet Fax Features				
Compatibility		to remote Internet Fax machines or emai uments sent via email from remote Intern		
Directory Access	Utilises the Unified Address Book			
Send/Receive	Send: Multi-page TIFF, PDF, PDF/A Receive: TIFF, MTIFF, PDF, PDF/A, PS, text	, PCL, PRN, JPEG		
Resolution	72 x 72 dpi to 600 x 600 dpi Bit Depth: 1-bit (black-and-white)			
Network Protocols	SMTP (send), POP3 (receive)			
Compliance	ITU-T T.37 compliant			
Walk-up Fax Features (Opti	onal; Customer-Installable – 1 and 2 lin	es)		
Compatibility	ITU (CCITT) Group 3			
Speed/Modems	One or Two V.34 modems: 33,600 bps. Le	ss than 4 seconds per page transmission t	ime	
Compression/Speed	MH/G3, MR/G3, MMR/SG3, JBIG/SG3			
Resolution	Walkup Send: Standard: 200 x 100 dpi Fine: 200 x 200 dpi Superfine: 600 x 600 dpi Receive: Accepts all sizes			
Fax Send Features	LAN Fax (fax from print driver) Auto Fax Transmission Reduction Page-by-page Job Status at the Machine Delay Start, Build Job, Favourites Automatic Memory Resend Automatic Cover Sheets PSTN Fax Batch Send (up to memory capacity) Device Address Book (up to 5,000 contact	is)		
Fax Receive Features	One- or Two-sided Printing Stapled or Unstapled Receive Print Mode – Manual (size, margin, stock, header)/Auto Output Tray Selection Up to 200 Password Protected Mailboxes Secure Receive Receive Timestamp Auto Answer Delay			
Fax forward	Forward to Email or SMB Location Fax Forward on Receive Only			
Fax Reports	Activity, Dial Directory, Group Directory, Transmission Confirmation, Pending Fax, Options Report, On Demand Overwrite Report, Mailbox Report, Broadcast Report			
Directory Access	Utilises the Unified Address Book Group fax available			
Auto Redial	Up to 14 attempts (per country requirements) 1 to 25 minute intervals			
Auto Resend	Up to 5 attempts			

Device Management			
Administrative Protocols	DHCP, BOOTP, SNMP, SLP [®] v2, HTTP, HTTPS, DHCP Autonet, TLS, NTP, DNS, SMB, SMTP/POP3, WSD, LDAP, Multicast DNS		
Management Support	SNMP Version 1. SNMP Version 2c and SNMP Version 3 trap over TCP/IP and IP MIB access (IETF-MIBII RFC 1213) Host Resources MIB RFC 2790, Printer MIB RFC 3805, PWG-Imaging-System- Power MIB, Configuration Orchestrator, Configuration Watchdog		
Xerox® CentreWare® Web	 A Web-based server application for network administrators that permits Web browser-based device management from any workstation, whether running on Windows, UNIX or any other operating system: Works with any SNMP-managed printer from any manufacturer Remote configuration of SNMP v3 Provides help with device discovery and installation, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management. Requires Windows 7 and Internet Explorer 6.0 and higher Auto-detect Xerox[®] CentreWare[®] Web server and download configurations files for touchless remote install 		
Xerox® Device Manager	 Xerox® Device Manager collects and manages the data that drives fact-based decisions for your enterprise device management environment. It is a single tool to install print queues and configure, manage, monitor and report on both networked and locally connected devices – regardless of vendor – across your enterprise. Xerox® Device Manager provides: Device monitoring and troubleshooting Remote configuration of SNMP v3 Extensive reporting and discovery of new devices Usage collection, chargeback and billing capabilities Auto-detect Xerox® Device Manager server and download configurations files for touchless remote install 		
Xerox [®] Workplace Cloud	Remote management to set and audit device configuration data with Xerox® Workplace Cloud, eliminating the need for an on-site server.		
Fleet Orchestrator	Fleet Orchestrator feature offers the ability to create a group of devices that share information with each other via a secure peer-to-peer connection. The following data can be shared: Software update files, clone files, and 1-Touch App files		
Novell NDPS/NEPS	Server gateway application: centralised management tool		
Xerox [®] Device Types for SAP Environment	Xerox, together with SAP through our Gold-level membership in the SAP Printer Vendor Programme, provides seamless connectivity between SAP system and your Xerox® Printers and Multifunction Printers. As an SAP customer, you benefit from having SAP-certified Xerox® Device types available right from SAP's online delivery model. SAP-certified device types for Xerox® Printers and Multifunction Printers are available to download. www.xerox.co.uk/en-gb/office/printer-software		
Xerox [®] Device Types for SAP R/3 Intelligent Bar- code Utility (optional)	Provides built-in process intelligence that allows the printing of barcodes on any appropriately configured PostScript printer in specific versions of SAP environment and within Latin-1 (ISO8859-1) SAP system code pages only. Used in conjunction with Xerox® PostScript Device Types for SAP environment and Xerox® Font Centre Barcode Fonts. Information available at www.xerox.co.uk/en-gb/office/printer-software		
Xerox® Barcode Pro PS (optional)	Enables intelligent PostScript printing on Xerox® Multifunction Printers by storing Xerox® Software, as well as the barcode fonts on the printer hard disk. Enables the printing of barcodes from any application (SAP client or mainframe) that supports PostScript printing. Information available at www.xerox.co.uk/en-gb/office/printer-software		
Xerox [®] Embedded Web Ser	ver – Integrated Device Web Pages Provided by the Device		
Device Status	Web server embedded in Network Controller: • Tray status/contents • Consumables status • Alerts • Remote Control Panel		
Job Submission	Print-ready files: PS, PCL, TIFF, PDF, JPG, TXT, PRN Output feature selection (2-sided, collate, orientation, staple, hole punch, folding, output destination) Delivery options (Immediate, sample set, delay and secure, Save job or reprint)		
Device Administration	Allows simple, remote installation setting of configuration options and management of the device, Fleet Orchestrator		
Browsers	Internet Explorer 10.x, 11.x Safari 10.x, 11.x Mozilla Firefox 45.x through 53.x Opera 25.x through 53.x Chrome 48.x through 72.x		
Support	Install print/scan drivers and online support available via support.xerox.com		
Languages Supported	International English, International French, Italian, German, International Spanish, Dutch, Brazilian Portuguese, Swedish, Norwegian, Danish, Finnish, Russian, Simplified Chinese, Korean, Japanese, Arabic		
Remote Services			
Xerox® Automatic Meter Readings (AMR)	Automates the process of collecting and submitting meter reads for tracking and billing of Xerox [®] Device usage. Eliminates the need for time-consuming end-user involvement and ensures that meter reads are submitted to Xerox on time.		
Xerox [®] Automatic Sup- plies Replenishment (ASR)	Automatically orders supplies for Xerox [®] output devices based on actual usage, eliminating the need to manually manage supplies inventory.		
Accounting			
Xerox® Standard Accounting (Standard)			
Xerox [®] Standard Accountin			
Xerox [®] Standard Accountin Tracking	Copy, Print, Fax, Scan and Email usage		

Xerox[®] AltaLink[®] B8145/B8155/B8170 Multifunction Printer

Accounting Options – Network Accounting (Allows central server to manage all accounting)			
	 Enhanced network accounting with up-to-the-minute data on how the system is being used Comprehensive management and enterprise-scale tracking and reporting of device usage of copy, print, scan and server fax Numerous solutions are available through Xerox Alliance Partners. For details visit www.xerox.co.uk Security enhancements with the addition of HTTPS protocol support Device requests account authentication from third-party server enabling larger databases of users and accounts Accept Authentication Login at control panel and pass to third-party Networking Account Interface with third-party accounting terminal for accounting user interface 		
Supplies	Description	Yield	
Toner Cartridge ⁷	Black	52,000 pages	
Transfer Belt Cleaner	1 Assembly	160,000 pages	
Second Bias Transfer Roll	1 Assembly	200,000 pages	
Staple Cartridges	For BR Finisher, Integrated Office Finisher, Office Finisher and Convenience Stapler (1 cartridge per carton)	5,000 each cartridge	
	For BR Booklet Maker (1 cartridge per carton)	5,000 each cartridge	
	For Office Finisher Booklet Maker (8 cartridges per carton)	2,000 each cartridge	
Staple Refills	For Integrated Office Finisher, Office Finisher, BR Finisher and Convenience Stapler (3 refills per carton)	5,000 each refill	
Xerox® Smart Kit®			
Drum Cartridge ⁹	1 Cartridge	200,000 pages	
Waste Toner Container w/o Suction Filter ¹⁰	1 Cartridge (AltaLink® B8145/8155)	121,000 pages	
Waste Toner Container with Suction Filter ¹⁰	1 Cartridge (AltaLink® B8170)	121,000 pages	

¹ Declared in accordance with ISO/IEC 24734.

² Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.

³ Available post-launch via software update. ⁴ Not available in all geographies.

⁵ Paper capacities are based on 20 lb./75 gsm stock; capacities will vary with different weight stocks.
⁶ Sold separately in some geographies.

7 Average standard pages. Declared in accordance with ISO/IEC 19752. Toner yield can vary due to many factors, including but not limited to, image area coverage, image content, media size, media orientation, run mode, application types, monthly print volumes and image quality set-points.

⁸ Under evaluation; certification expected in Q2 2021.

⁹ Average drum yield is based on a run length of 5 pages of 8.5 x 11 in./A4 LEF pages, with split of 35 % color/65 % black-and-white pages.
 ¹⁰ Waste Toner Container yield will vary depending on type of image, area coverage % and Job run length.

¹¹ With optional Hard drive.

Return spent imaging supplies through the Xerox Green World Alliance collection/reuse/recycling programme. For more information, visit www.xerox.co.uk/recycling.

For more information, visit us at www.xerox.co.uk/office.

